Oppland stål

CE 0402

DECLARATION OF PERFORMANCE (DoP)
YT-FS-01
FlexSafe 0402 - CPR - SC0226-15

Manufacturer:	Oppland Stål AS Ottadalsvegen 1630, N-2682 Lalm, Norge Phone: +47 61 23 93 30 / Web: www.Opplandstaal.no
Name of product	FlexSafe
Product type	Bridge parapet type FlexSafe H1200
Intended use	Road restraint system by roads and vehicle circulation areas
Harmonized standard	EN 1317-5:2007+A2:2012
System of assessment and verification	System 1
Name of notified body	RISE Research Institutes of Sweden
Identification number of the notified body	0402
Notified body tasks	The notified body has performed the initial type testing for the relevant characteristics of the product, initial inspection of the factory and of the factory production control (FPC), and performs continuous surveillance, assessment and approval of the factory production control
Certificate of conformity (COC)	0402-CPR-SC0226-15

Declared performance

Essential characteristics	Performance	Harmonized standard
Containment level	H2	EN 1317-5:2007+A2:2012
Impact severity level	B	EN 1317-5:2007+A2:2012
Normalized workingwidth for containment test	W2 (0,7m)	EN 1317-5:2007+A2:2012
Normalized working width for TB11 test	WP1 ≤ 0,6	EN 1317-5:2007+A2:2012
Normalized dynamic deflection	0,6m	EN 1317-5:2007+A2:2012
Normalized vehicle intrusion	VI12 ≤ 0,8	EN 1317-5:2007+A2:2012
Resistance to snow removal	Class 4	EN 1317-5:2007+A2:2012
Durability	Hot dip galvanized coating according to EN ISO 1461	EN 1317-5:2007+A2:2012

The performance of the product is on conformity with the declared performance.
This declaration is issued under the responsibility of the manufacturer

Signed for, and on behalf of the manufacturer *Ken-Runar Haugen-Kind*
- *Quality Manager*

Lalm 2018.13.11

Ken-Runar Haugen-Kind